

WALLMax[®]

Panel Wall Fencing



10 Year Warranty*



Termite Proof



Easy Maintenance



Strength & Durability



Noise Reduction



Insulated No Heat Transfer



Economical Compared To Masonry Walls



Asbestos Free



MK FENCE SUPPLY

WALLMax®

Panel Wall Fencing

WALLMax® Panel Wall Fencing is suitable for both residential and commercial applications. A modular Colorbond® sided infill panel set between large pillar style posts with capping, fabricated from strong corrosion resistant aluminium.

Being both sturdy and stylish this wall also offers a unique sound barrier between neighbours or commercial situations.

The infill panel comes in two colours Basalt® Matt or Surfmist® Matt. There is also a Primed panel which can be finished in a variety of coatings and unlimited colours.

A masonry appearance wall is achieved with no footings required.

WALLMax® offers prestige styling, privacy and a very cost effective solution for sound control.

Painting

WALLMax® Basalt® Matt or Surfmist® Matt infill panels require no painting, giving a sleek modern look right after installation. An elegant finished surface can also be achieved with our Primed WALLMax® infill panels by applying either a smooth or textured exterior coating. Textures ranging from smooth (simulating the modern rendered look) to a heavily bold surface are appealing. All posts and capping are pre-coated in Basalt® or Surfmist®.

WHY CHOOSE WALLMax®?

- No masonry cracks – allows for ground movement
- Lightweight product – no heavy, dangerous tilting
- DIY system – very simple
- No strip footings – low cost, no mess, no hassle
- Economical – compared to masonry & concrete walls
- Very sturdy – avoid rotting, warping, dents & corrosion
- Quiet – superior noise reduction up to 20+dB
- Insulated – cool, no heat transfer
- Easy to coat – smooth wall surface, pre-primed posts
- Modular – design and build your own style
- Can include decorative powder coated or TimberSLAT™ Louvres. Fixed or adjustable.
- Combat the elements – termite resistant and the Polystyrene core contains a Fire Retardant
- Transport efficient – lightweight components



SPECIFICATIONS

Panels

Panel sizes available: 2400mm wide x 1200, 1500, 1800, 2100 or 2400mm high (doesn't include post width)

The infill panels are manufactured with two layers of Colorbond® steel, with a 50mm thick Polystyrene core. For panel heights above 1200mm each infill panel interlock forming a sleek shadow line, no separate joiner is required.

The core is Polystyrene EPS FR which contains a Fire Retardant and conforms to a Bushfire Attack Level (BAL) rating of BAL40. Asbestos free and CE compliant



Posts

Post sizes available: 2.5mm thick x 150mm square or 2.5mm thick x 200mm square. The posts are extremely strong due to their aluminium extruded design with a thickness of 2.5mm. Each 150mm or 200mm Square.

Both posts and capping are pre painted Basalt® or Surfmist®.

Size and depth of hole required: 1800mm to 2100mm high panels require posts to be 900mm in ground with 400mm diameter hole. 2400mm high panels require posts to be 1000mm in ground with 400mm diameter hole.



WALLMax65

Panel Wall Fencing

Paired with our ColorMAX® channel posts, WALLMax65™ narrow profile, making it a great alternative to conventional Boundary Fencing.



DESIGN YOUR FENCE....



Manufactured using BlueScope® Steel for our panel skins ensures a quality Australian steel product.

